

# Declaration of Performance (DoP)

No. F162-CPR-20130821 (Revision 1)	
Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number: [Article 11-4]	<b>Jøtul F 160 Series</b> (Jøtul F 162, Jøtul F 164, Jøtul F 166)
Intended use of the product:	Roomheater burning solid fuel without water supply
Name and Address of the manufacturer:	Jøtul AS
[ Article 11-5]	Postboks 1411, 1602 Fredrikstad, Norway
	Tel.: +47 69 35 90 00
	E-mail: post@jotul.no
Contact address: [Article 12-2]	No relevance
AVCP:	System 3
<i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i>	
Notified body:	RWE Power AG, Feuerstättenprüfstelle
	NB-No 1427
Test report no:	FSPS-Wa 1985-EN, FSPS-Wa 2154-EN
Declared performance:	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	-
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm
	<b>F 162, F 164, F 166</b>
	Rear = 200
	Sides = 700
	Corner = 500
	Front = 1000
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,06 %]
	NOx [128 mg/m <sup>3</sup> ]
	OGC [63 mgC/m <sup>3</sup> ]
	Dust [20 mg/m <sup>3</sup> ]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [209°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	5 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [83%]

**Declaration:**

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed on behalf of the manufacturer:**

Anna K. Øren  
R&D Manager

---

*(Name and function)*

Fredrikstad, 26.06.2018

---

*(Place and date of issue)*



---

*(Signature)*