

EN



## Declaration of performance

DoP F200V2-F205V2-CPR-200325

### PRODUCT

Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 200 V2, Jøtul F 205 V2
Intended use:	Roomheater burning solid fuel without water supply
Fuel	Wood logs

### MANUFACTURER

Name:	Jøtul AS
Address:	Postboks 1411 1602 Fredrikstad, Norway
Telephone:	+47 69 35 90 00
Email:	<a href="mailto:post@jotul.no">post@jotul.no</a>

### CHECKS

According to AVCP:	System 3
Notified body:	Danish Technological Institute
NB-No:	1235
Test report no:	300-ELAB-2739-EN
Harmonized norm:	EN 13240:2003:AC:2006/A2:2004:AC:2007

### SAFETY

Safety distance to combustible materials	Minimum distances [in mm] - (F 205 V2)
	Rear = 125
	Sides = 400 (425)
	Corner = 225 (250)
	Front = 750
	Floor = 0
	Ceiling = 750
	Also see the installation instructions
Fire safety	Pass
Reaction to fire	A1
Risk of burning fuel falling out	Pass
Surface temperature	Pass
Electrical safety	-
Release of dangerous substance	x
Cleanability	Pass
Maximum water operating pressure	-
Mechanical resistance (to carry a chimney/flue)	x

## PERFORMANCE AND EMISSION

Essential characteristics	Performance
Emission of combustion products	Pass
CO	[0,0787 %], 984 mg/Nm <sup>3</sup>
NOx	99 mg/Nm3
OGC	56 mg/Nm3
PM	14 mg/Nm3
Flue gas temperature at the measuring section at nominal heat output [in °C]	269
Flue gas outlet temperature at nominal heat output [in °C]	323
Thermal output	Pass
Nominal heat output	5 kW
Nominal space heat output	5 kW
Nominal water heat output	-
Energy efficiency	$\eta$ [82%]
Durability	x

### Declaration:

The performance of the product is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

**Signed on behalf of the manufacturer:**

Espen Auensen

R&D Manager

*(Name and function)*

Fredrikstad, March 2025



*(Signature)*